Initial Wash

DO NOT use abrasive or harsh chemicals or natural cleaning solutions to clean your System. Simply rinse with hot water.

DO NOT use any scrubbing agents such as steel wool pads, brushes or sponges. Simply rinse with hot water.



NOTE: The Plunger must NEVER be placed upright on any surface. In order to ensure the integrity of the seal ALWAYS set the Plunger on its side and ALWAYS secure it against a stationary object to avoid rolling.

NOTE: The System MUST air dry. Paper towels and cloth leave fibers that will clog the holes in the bottom of the Juice Container and be unsanitary.

1. To ensure the integrity of the seal set the Plunger on its side in the sink. Spray it with hot water.



2. To dry the Plunger secure it against a stationary object or leave it in the sink to avoid rolling.



3. Rinse the Juice Container with hot water.



4. Turn the Juice Container on its side to air dry.



5. Wipe the Stabilizer Arm with a damp cloth. In order to ensure the integrity of the electrical components DO NOT rinse or immerse in water.



6. Allow the Stabilizer Arm to air dry.



7. When the Plunger and the Juice Container are dry, place the Juice Container on a hard surface with the label facing the operator.



8. Grasp the Plunger Rod with both hands and match the largest hole in the Plunger Plate to the largest Guide Post protruding upward from the bottom of the Juice Container.



9. Lower the Plunger over the Guide Posts.



10. With both hands gently lower the Stabilizer Arm onto the Plunger Rod until the Arm rests on the rim of the Juice Container.



11. Store the Automated Juice Dispenser in a safe, dry place.



NOTE: DO NOT store any objects on top of the Automated Juice Dispenser.